

???????????? H3C S5130S-EI (48*GLAN 4*SFP+)



LS-5130S-52ST-EI-GL



????????? 48-????????? ?????????? H3C S5130S-52ST-EI L2 Ethernet Switch with 48*10/100/1000Base-T Ports and 2*10G BASE-X SFP+ Ports and 2*1/2.5/5/10G BASE-T Ports,(AC)

?????????: ??? ????
????
???? 44100 ???

[?????? ?????? ?? ??????](#)

????????? Network standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3z
LED Indicator	1* Power,24* Link/Act,4*Mode
Interfaces	48*10/100/1000 Base-T Ethernet ports (Auto MDI/MDIX)
Transmission media	4*1000 Base-X SFP ports (Combo) Recommended: CAT5/5e UTP or better
Fan quantity	N/A

Dimensions	440.0mmx178.0mmx44.0 mm
Material	Metal
Level of protection	Lightning protection for uplink ports: 6KV Lightning protection for power: 6KV ESD: Air discharge: ±10kV Contact discharge: ±8kV
Forwarding mode	Store-and-forward
Switch capacity	48Gbps
Forwarding rate	35.60Mpps
Buffer	2Mb
MAC address table	8K
Power method	Input: 100-240V AC 50/60Hz
Power consumption	